

Home / Standard products / Edge protector- and sealing-profiles / Edge protector, Silicone, with wire carrier




- Temperature resistant from -60 °C to +200 °C
- Tolerances in accordance with DIN ISO 3302-1 E2
- Further versions also available with various fire protection tests for the railway industry in accordance with EN 45545-2, DIN 5510-2, NF F 16 101 and BS 6853.

Illustration	Art. No.	Colour	Clamping range	Material	Clamp fitting	PU	Weight
			[mm]			[m]	[g/m]
7	0600195	black	1,0 - 2,0	silicone	wire carrier	50	80
14.5	0600020	black	2,0 - 4,0	silicone	wire carrier	100	160

Illustration	Art. No.	Colour	Clamping range	Material	Clamp fitting	PU	Weight
14,0	0600263	black	5,0 - 8,0	silicone	wire carrier	100	244

 $\ ^{\odot}$  2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0



## **Cookie-Settings**

☐ Technically essential ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on "Agree and continue" or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our <u>data privacy statement</u>.

Agree and continue Accept only essential