



- Inner tube: EPDM, black, smooth
- Cover: EPDM, black, fabric pattern
- Reinforcement: synthetic textile inlay
- Operating pressure: 6 bar
- Burst pressure: 18 bar
- Temperature: -30 to +100°C
- EN 45545-2 (R22/R23, HL2) water loaded
- DIN 5510-2 (S4, SR2, ST2)

Art. No.	Inner-Ø x Wall [mm]	Weight [g/m]	Roll length [m]
0800322	9 x 3,5	170	40
0800229	10 x 4,5	250	40
0800245	13 x 3,5	250	40
0800209	15 x 3,5	280	40
0800305	18 x 3,5	330	40
0800020-1	20 x 3,5	360	40
0800120	22 x 4,5	480	40
0800246	25 x 3,5	430	40

Art. No.	Inner-Ø x Wall [mm]	Weight [g/m]	Roll length [m]
0800142	28 x 4,0	520	40
0800247	32 x 4,0	590	40
0800248	35 x 4,0	640	40
0800249	38 x 4,0	700	40
0800219	42 x 5,0	1.000	40
0800250	50 x 5,0	1.180	40
0800143	60 x 5,0	1.400	40

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

Cookie-Settings

☒ Technically essential
☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our data privacy statement.

Agree and continue Accept only essential