



[Home](#) / [Standard products](#) / [Rubber hoses](#) / [Heavy duty oil and fuel delivery hose EN 12115:2011](#)



- mandrel-built
- Inner tube: NBR, oil-resistant, black, smooth, antistatic
- Cover: CR, black, smooth, fabric pattern
- Reinforcement: Textile cord inlay, crossing antistatic wire
- Operating pressure: 16 bar
- Burst pressure: 64 bar
- Vacuum force: 9 mwp
- Temperature: -40 to +100°C
- Application: mineral oil hose for road tanker and storage tanks

Art. No.	Inner Ø x Wall [mm]	Operating pressure [bar]	Burst pressure [bar]	Bending radius [mm]	Weight [kg/m]
0800056	19 x 6,0	16	64	150	0,65
0800227	25 x 6,0	16	64	200	0,82
0800220	32 x 6,0	16	64	255	1,00
0800072	38 x 6,5	16	64	305	1,20
0800066	50 x 8,0	16	64	405	2,00
0800221	63 x 8,0	16	64	505	2,39

Art. No.	Inner Ø x Wall [mm]	Operating pressure [bar]	Burst pressure [bar]	Bending radius [mm]	Weight [kg/m]
0800083	75 x 8,0	16	64	605	2,85
0800105	100 x 8,0	16	64	815	3,50

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential