



[Home](#) / [Standard products](#) / [Rubber-to-metal elements](#) / [HIL-friction-wheels](#)

Drive element in mechanical engineering and in conveyor technology

- Material highly wear-resistant polychloroprene, 80  $\pm$ 5 Shore A
- Friction wheel hub made of 1.0711 (9S20K)
- Permissible friction lining temperature -30° C to +70° C
- Centre holes on both sides for drive locating purposes



Art. No.	D	b	d	B
	[mm]	[mm]	[mm]	[mm]
0500286	40	10	25	13
	45	11	28	14
0500282	50	12	32	16
	56	14	35	18
0500275	63	16	40	20
	71	18	45	22
	80	20	50	25

Art. No.	D	b	d	B
	90	22	55	27
0500271	100	25	65	30
	112	28	70	33
0500276	125	32	80	37
0500293	140	36	90	41
0500195	160	40	100	45

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

[+49 \(0\) 5121 / 28995-0](tel:+495121289950)

[E-Mail](#)

## Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential