



[Home](#) / [Standard products](#) / [Plastic hoses and -tubes](#) / [Plastic tube, resistant to welding spatter](#)



Material polyurethane for welding applications

- According to drawing 39D 1475
- Temperature range from -40 °C to +90 °C
- Vacuum force: 0.9 bar
- Resistant to welding spatter (SSB)
- Flame-retardant in accordance with UL 94-V0, outside calibrated
- Halogen-free and hydrolysis-resistant
- For use with drag chains
- Very good abrasion resistance

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2800023	4	1	16	7	12	100
2800024	6	1	16	14	22	100
2800026	8	2	16	15	47	100
2800027	10	2	16	20	66	50
2800028	12	2	16	28	85	50
2800029	14	2	16	45	100	50

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
2802051	16	2,5	16	55	134	50

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2800023B	4	1	16	7	12	100
2800024B	6	1	16	14	22	100
2800026B	8	2	16	15	47	100
2800027B	10	2	16	20	66	50
2800028B	12	2	16	28	85	50
2800029B	14	2	16	45	100	50
2802102B	16	2,5	16	55	134	50

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2800023G	4	1	16	7	12	100
2800024G	6	1	16	14	22	100
2800026G	8	2	16	15	47	100
2800027G	10	2	16	20	66	50
2800028G	12	2	16	28	85	50
2800029G	14	2	16	45	100	50
2802102G	16	2,5	16	55	134	50

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
-----------------	----------------	-----------------------	---------------------------	-----------------------	---------------	--------------------

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2800023R	4	1	16	7	12	100
2800024R	6	1	16	14	22	100
2800026R	8	2	16	15	47	100
2800027R	10	2	16	20	66	50
2800028R	12	2	16	28	85	50
2800029R	14	2	16	45	100	50
2802102R	16	2,5	16	55	134	50

Art. No.	Inner Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2800023W	4	1	16	7	12	100
2800024W	6	1	16	14	22	100
2800026W	8	2	16	15	47	100
2800027W	10	2	16	20	66	50
2800028W	12	2	16	28	85	50
2800029W	14	2	16	45	100	50
2802102W	16	2,5	16	55	134	50

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

[+49 \(0\) 5121 / 28995-0](tel:+495121289950)

[E-Mail](#)

Cookie-Settings

- Technically essential
- Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential