



[Home](#) / [Standard products](#) / [Plastic hoses and -tubes](#) / [Polyamide tube](#)



for use as a pneumatic line with quick-fit connectors.

- According to dwg. 39-V-16663
- Material PA 12, soft, natural colours
- In accordance with DIN 73378
- Working pressure range from -0,9 to 16 bar
- Temperature resistant from -40 °C to +90 °C
- Abrasion 30 mm³ in accordance with DIN 53516

Art.-No.	Outer Ø	Wall thickness	Weight	Roll length
	[mm]	[mm]	[g/m]	[m]
2601561	4	1	10	100
2601562	6	1	16	100
2601565	8	1,25	28	100
2601566	10	1,25	35	100
2601567	14	1,5	60	100
2601569	20	2	123	100

Further sizes upon request

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential