



[Home](#) / [Standard products](#) / [Rubber hoses](#) / [Tempering hose, rubber](#)



- With textile inlay
- For individual applications, especially in the injection moulding sector
- For conducting air, cooling water and demineralized water with corrosion protection
- For use without hose clamps
- Temperature range: Air: - 40 to + 75°C
- Temperature range: Water: - 40 to + 120°C
- Free from any substances which can affect paint adhesion (following PV 3.10.7)

Find out more in our Flyer about the Push-Lock-hose program:



[Product sheet Push-Lock
hose and Fittings](#)

Art. No.	DN	Operating pressure [bar]	Bending radius [mm]	Weight [g/m]	Roll length [m]
1006024-TS-B	6	16	45	125	40
1006025-TS-B	10	16	75	150	40
1006026-TS-B	13	16	90	235	40
1006027-TS-B	16	16	115	350	40

Art. No.	DN	Operating pressure [bar]	Bending radius [mm]	Weight [g/m]	Roll length [m]
1006024-TS-R	6	16	45	125	40
1006025-TS-R	10	16	75	150	40
1006026-TS-R	13	16	90	235	40
1006027-TS-R	16	16	115	350	40

You will find the corresponding fittings under [hose fittings](#). Please do not hesitate to [contact](#) us if you have any questions.



© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential