



[Home](#) / [Standard products](#) / [Plastic hoses and -tubes](#) / [PVC fabric hose](#)



Soft PVC fabric hose, for conducting liquid and air

- Temperature range: -20 °C to +65 °C
- Tolerances in accordance with DIN 16940
- Pressure: tested in accordance with DIN EN ISO 1402-7.3
- Technical data at an ambient temperature of 20 °C
- Suitable for food, categories A, B and C

Art. No.	Inner Ø	Outer Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2300074	4	10	3	28	15	84	50
2300075	5	11	3	28	18	96	50
2300100	6	12	3	25	25	108	50
2305894	8	14	3	24	30	132	50
2300009	9	15	3	22	35	144	50
2300027	10	16	3	21	40	156	50
2300073	12	18	3	17	55	180	50
2300012	12	21	4,5	17	55	297	50
2300076	12,5	18,5	3	15	55	186	50
2300015	13	19	3	15	70	192	50
2300014	13	20	3,5	16	72	231	50
2300077	15	21	3	15	75	216	50
2300016	16	23	3,5	15	75	273	50
2300078	16	24	4	15	75	320	50
2300017	19	26	3,5	10	130	315	50

Art. No.	Inner Ø	Outer Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
2300072	19	27	4	11	130	368	25/50
2300079	25	33	4	9	200	464	25/50
2300018	25	34	4,5	8	220	531	25/50
2300081	30	38	4	7	250	554	25/50
2300024	32	42	5	8	310	740	25/50
2300082	38	48	5	6	420	860	25/50
2300083	45	55	5	4	550	1000	25/50
2300084	50	60	5	4	650	1100	25/50

Art. No.	Inner Ø	Outer Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2300032	6	12	3	15	25	108	50
2300033	9	15	3	12	35	144	50
2300031	10	16	3	10	40	156	50
2300034	13	20	3,5	8	60	231	50
2300035	19	27	4	7	110	368	50

Art. No.	Inner Ø	Outer Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2300036	6	12	3	15	25	108	50
2300037	9	15	3	12	35	144	50
2300021	10	16	3	10	40	156	50
2300038	13	20	3,5	8	60	231	50

Art. No.	Inner Ø	Outer Ø	Wall thickness	Operating pressure	Bending radius	Weight	Roll length
	[mm]	[mm]	[mm]	[bar]	[mm]	[g/m]	[m]
2300039	6	12	3	15	25	108	50
2300040	9	15	3	12	35	144	50
2305887	10	16	3	10	40	156	50
2300041	13	20	3,5	8	60	231	50
2300042	19	27	4	7	110	368	50



© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential