



[Home](#) / [Standard products](#) / [Rubber balls](#)

---



We offer you a wide range of rubber balls of different materials (CR, EPDM, NR, NBR, SBR, PUR, FKM, silicone) in the hardness range from 30  $\pm$ 5 Shore A to 90  $\pm$ 5 Shore A.

Combinations of different materials enables a precisely targeted application of the rubber balls. Furthermore the industrial balls cannot only be produced in solid version but also with different cores of metal, aluminium, plastic (hollow or solid), cork or wood.

Rubber balls are primarily used in two areas of application.

- As locking pieces in valves, pumps and conduits, whereby material and valve seat have to be adjusted to each other. A proper sealing of the valve ball is determined by the ball weight, which will be achieved by choosing a suitable material or a core of metal, aluminium, plastic (hollow or solid), cork or wood.
- As sieve cleaning balls in sieving equipment (e.g. tumbler sieving machines). The rubber balls used here have a high abrasion resistance as well as a good rebound elasticity (NR, NBR, PUR, silicone).

Available balls of all above mentioned materials with **sizes from 5 mm Ø to 300 mm Ø**

© 2023 Hilgendorf GmbH + Co. KG • Benzstraße 1 • D-31135 Hildesheim

+49 (0) 5121 / 28995-0

E-Mail

## Cookie-Settings

- ☒ Technically essential
- ☐ Statistical purposes (anonymised)

We use cookies on our website. Some of them are technically essential, while others enable us to provide you with a better user-experience. You can consent to the use of cookies for statistical purposes by clicking on „Agree and continue“ or adjust the settings on your own via the options above. For further information and how you can change your decision at any time, please refer to our [data privacy statement](#).

Agree and continue Accept only essential