



Kühlwasserschlauch nach DIN 73411-79

- Dorngewickelte Ausführung
- Seele: EPDM, schwarz, glatt
- Decke: EPDM, schwarz, stoffgemustert
- Druckträger: Textilcordeinlage
- Temperaturbereich: -40° C bis +120° C



Art.-Nr.	Innen-ø x Wand [mm]	Betriebsdruck [bar]	Gewicht [g/m]	Rollen-Länge [m]
0750119	6 x 3,5	6	130	40
0800010	8 x 3,5	6	150	40
0800020	20 x 3,5	6	300	40
0800128	22 x 3,5	6	320	40
0800123	25 x 3,5	6	360	40
0800008	28 x 4,0	6	420	40
0800230	30 x 4,0	6	460	40
0800231	32 x 4,0	6	490	40
0800021	35 x 4,0	6	540	40
0800077	38 x 5,0	6	780	40
0800041	40 x 5,0	6	820	40
0800109-1	42 x 5,0	6	850	40
0800081	45 x 5,0	6	900	40
0800093	48 x 5,0	6	960	40
0800051	50 x 5,0	6	1.000	40
0800232	55 x 5,0	6	1.100	40
0800092	60 x 5,0	6	1.200	40
0800234	63,5 x 5,0	5	1.250	40
0800074	65 x 5,0	5	1.260	40
0800233	70 x 5,0	5	1.350	40



Kühlwasserschlauch nach DIN 73411-79

Art.-Nr.	Innen-ø x Wand [mm]	Betriebsdruck [bar]	Gewicht [g/m]	Rollen-Länge [m]
0800075	75 x 5,0	5	1.460	40
0800235	80 x 6,0	4	1.730	20
0800236	85 x 6,0	4	1.750	20
0800237	90 x 6,0	4	2.200	20
0800078	100 x 6,2	3	2.400	20
0800239	110 x 6,0	3	2.560	20
0800238	114 x 6,0	3	2.580	20
0800240	120 x 6,5	3	3.150	20
0800241	125 x 6,5	3	3.200	20
0800242	140 x 6,5	3	3.540	20
0800243	152 x 7,0	3	3.800	20
0800110	160 x 7,0	3	4.100	20
0800244	200 x 7,5	3	5.050	20



Kühlwasserschlauch nach DIN 73411-96

- extrudierte Ausführung
- Seele: EPDM, schwarz, glatt
- Decke: EPDM, schwarz, glatt
- Druckträger: Aramidgarn
- Temperaturbereich: -40° C bis +130° C



Art.-Nr.	Innen-ø x Wand [mm]	Betriebsdruck [bar]	Gewicht [g/m]	Rollen-Länge [m]
0800017	10 x 3,5	10	150	50
0800011	12 x 3,5	10	160	50
0800085	13 x 3,5	10	170	30
0800314	15 x 3,5	10	190	30
0800007	16 x 3,5	10	200	30
0800212	18 x 3,5	10	230	30
0800027-1	19 x 3,5	10	240	30



Kühlwasserschläuche brandschutzgeprüft nach EN 45545-2

- dorngewickelte Ausführung
- Seele: EPDM, schwarz, glatt
- Decke: EPDM, schwarz, stoffgemustert
- Druckträger: synthetische Textileinlage
- Brandschutzeinstufung nach:
 - EN 45545-2 (R22/R23, HL2)
 - DIN 5510-2 (S4, SR2, ST2) (ungültig)
- Temperaturbereich: -30° C bis +100° C



Art.-Nr.	Innen-ø x Wand [mm]	Betriebsdruck [bar]	Gewicht [g/m]	Rollen-Länge [m]
0800322	9 x 3,5	6	170	40
0800229	10 x 4,5	6	250	40
0800245	13 x 3,5	6	250	40
0800209	15 x 3,5	6	280	40
0800305	18 x 3,5	6	330	40
0800020-1	20 x 3,5	6	360	40
0800120	22 x 4,5	6	480	40
0800246	25 x 3,5	6	430	40
0800142	28 x 4,0	6	520	40
0800247	32 x 4,0	6	590	40
0800248	35 x 4,0	6	640	40
0800249	38 x 4,0	6	700	40
0800219	42 x 5,0	6	1.000	40
0800250	50 x 5,0	6	1.180	40
0800143	60 x 5,0	6	1.400	40